



DC-420

# **Collect, Exchange and Back-up On-site Data.**

With DC-420, retail operators can securely access and exchange data to automatically collect and update pricing, sales and inventory information. Powered by an Intel® Celeron® processor, it seamlessly transfers LPA, foodservice, POS and automatic tank gauging (ATG) data to back-office and analytics systems.

### **KEY FEATURES**

- Real-time Analytics
- Rapid Deployment (Plug-and-Play)
- Centralized Configuration and Management
- Continuous Monitoring and Remote Access
- Offline Processing and Self-Correcting







## DC-420 **DATA SHEET**

#### **Basic Information**

DC-420	
DATA SHEET	
Basic Information	LAN WAN CONTRACTION OF C
CPU	Onboard Intel Celeron J4105/N4100/J4125(DDR4)
TDP	10W %
BIOS	American Megatrends Inc.
Chipset	Intel Gemini Lake
Memory	1 x SO-DIMM DDR4 Slot Support 4GB DDR4/LPDDR4 upto 2400 MT/s
OS	Windows 7/Windows 8/Windows 10/Linux
Audio	Intel High Definition Audio Controller
Network	2 x RTL8168/8111/8112 Gigabit Ethernet Controller 10/100Mbps/1000Mbps BaseT LAN
Video	Intel® UHD Graphics 600
<b>C</b>	

#### Storage

MSATA	1 x M-SATA3.0 slot for MSATA SSD, support 6Gb/s
M.2	1 x M.2 slot for M.2 NGFF SSD, support 6Gb/s(customized for bulk order only)
SATA	1 x SATA3.0 slot for SATA HDD or SSD, support 6Gb/s

#### Wi-Fi

Module

#### Input/Output Ports

Switch	1 x Power On/Off Switch
LED	2 x LED
USB	4 x USB3.0
Display	1 x VGA, 1 x HDMI
LAN	2 x RJ45 Giga LAN
СОМ	2 x RS232 COM

#### **Power and Working Environment**

Input	DC100-240V AC/50-60Hz
Output	DC 12V/5A
Operating Temperature	-10/+60 °C, 14/+140 °F
Storage Temperature	-20/+85 °C, -4/+185 °F
Relative Humidity	10%~90% (non-condensing)

Product Dimension and Detail		
Size	135*127*39 mm (44 mm with foot	
	pad), 5.31*5*1.54 inch	
Weight	Net 0.55 kg, Gross 1.2 kg (Net 1.21	
	lbs, Gross 2.65 lbs)	
Shell	Black color aluminum alloy	
Cooling Mode	Fanless	
Functions	Auto Power On, RTC, WOL, PXE	





Petrosoft LLC, 290 Bilmar Drive, Pittsburgh, PA 15205, USA 412-306-0640 info@petrosoftinc.com

Copyright © 2021 Petrosoft Inc. All Rights Reserved. Trademarks are the property of Petrosoft and the respective companies. Petrosoft is not responsible for errors and omissions.